

UNITED FISHING OIL

Product Description

Hydrotreated fishing diesel engine oil is a high quality diesel engine oil designed to meet the lubrication requirements of many type of diesel engines especially those used for small vessels like fishing boats etc. It provides outstanding protection for diesel engines running at high temperature and using fuel with high level of sulfur content.

Fishing Diesel engine oil is a performance product which is optimized to provide maximum control of carbon deposit, minimum oil consumption and best neutralizing ability for not only new engine design. Its high alkaline reserve neutralizes harmful combustion by-products when engine burning diesel with higher sulfur content.

Applications / Benefits

- * Maintains piston cleanliness and reduces oil consumption
- * Delivers high performance in small shipborne diesel engines
- * Effectively neutralizes acids generated from high-sulfur fuels
- * Provides superior protection against ring and cylinder wear

Typical Characteristics

Test Description	Method	Unit	
SAE Viscosity Grade	SAE J 300	-	15W40
Density @ 15 °C	ASTM D 4052	kg/L	0.886
Flash Point	ASTM D 92	°C	222
Pour Point	ASTM D 97	°C	-27
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	116.0
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	15.3
Viscosity Index	ASTM D 2270	-	138
TBN	ASTM D 2896	mgKOH/g	15

Suggested for the Following Uses

- * API CF-4/SG
- * MIL L-2104C

Reference No.
4160G2CF4SGREV0

Last revised date:
16-10-25